



TECHNICAL DATA SHEET

Special Mortar

RJ 2.07

Conservation Mortars:	Non-hydraulic stone repair mortars produced from mature Chalk lime putty mixed with stonedusts and sand, colour and texture matched to the stone to be repaired. The repaired stone is often then treated with sheltercoat itself colour-matched to the stone. Deep repairs are normally filled with a coarse repair mortar prior to the application of the surface repair mortar.
Ash Mortars:	Ash mortars are a blend of mature Chalk Lime Putty and sieved coal ash designed to match Victorian ash pointing mortars. Early historic mortars normally have ash inclusions as kiln-fuel residue, and coal ash or charcoal particles are often added to repair mortars to match this.
Brick Repair Mortars:	Brick repair mortars are a blend of mature lime putty and sand but normally require the addition of pigments for an accurate colour match.
Environment:	Lime Putty mortar is an environmentally sustainable product.
Availability:	25kg Heat-sealed bags and 15 litre tubs. Mixed to order.
Shelf Life:	Unlimited. Matures with age. Lime putty mortars stiffen during storage, but can be plasticised without the addition of water by thorough re-mixing.
Observations:	<p>The use of stone and brick repair mortars is a skilled operation normally undertaken by an experienced conservator. Non-hydraulic lime mortars do not perform as modern hydraulic lime and cement, and set only by reaction with atmospheric carbon dioxide in the presence of moisture. This 'carbonation' is a slow process and control of the drying and curing process by 'tending' and protecting is crucial to success and long-term performance.</p> <p>Protections are essential. Do not use if there is risk of frost.</p>



Health & Safety:

See Health and Safety Data Sheet RJ 5.02.
CALCIUM HYDROXIDE Ca(OH)_2 Alkali (pH 13).
CAS No 1305-62-0. EINECS No 215-137-3.
Danger: H318 Causes Serious Eye Damage.
Warning: H315 Causes skin irritation.

Technical Data:

RJ 2.03 - Use of Lime Putty Bedding + Pointing Mortars

Technical Advice:

From our Technical Department 01935 83676
info@roseofjericho.co.uk
Product + H & S data can be printed from our web site:
www.roseofjericho.co.uk

Disclaimer:

The information provided in this product data sheet and all technical advice is for guidance and is given in good faith but without warranty, since the site conditions and care and skill of application are beyond our control. We can accept no liability for the performance of our products, beyond the value of the material supplied. This does not affect your statutory rights.