

## TECHNICAL DATA SHEET

## Water Based Eggshell

RJ 4.10A

**Description:** High quality mid-sheen quick drying water-based acrylic paint. Artist

quality earth and traditional powder pigments provide matchless purity and quality of colour with subtle variations of colour and tone. It is NOT a permeable paint, and is not to be used on newly plastered surfaces

or solid walls that need to breathe.

Environmental Contains no added lead Actual VOC content <5g/l. 2010 EU limit

Considerations: 100g/l. All Rose of Jericho paints comply with the latest environmental

legislation.

Usage/Purpose: Normally used for the decoration of joinery and woodwork. For interior

use only. Rose of Jericho Water Based Eggshell is not as wipeable as

Oil Eggshell.

Finish: Mid-sheen with subtle variations in colour and tone. All Rose of Jericho

paints are made using powder pigments. Colour and tone variations due to these pigments and differing porosity of surfaces are inevitable. The intention is that our eggshell paints possess the lack of uniformity and

charm of traditional oil paints.

Colours: Water Based Eggshell is available in all colours plus white.

Availability: 1 litre and 2.5 litre cans. Mixed to order.

Fire Rating: Non-Flammable.



Health & Safety
Information:

Detailed information is provided in Safety Data sheet RJ 5.07B. Those engaged in the use and application of this product should ensure they read this Safety Data sheet.

Sensible Precautions: Keep out of reach of children. Protect from frost, extremes of temperature and direct sunlight. Avoid contact with skin and eyes and inhalation of vapours. Use in good natural ventilation and wear protective equipment and clothing. Wear suitable respiratory protection in confined spaces.

Storage:

Store upright in secure dry conditions inaccessible to children and animals. Keep out of direct sunlight and away from sources of ignition. Containers should be kept closed during storage. Avoid spillage.

Composition:

Artist quality powder pigments in acrylic copolymer dispersion.

Solvent: Water.

Performance:

Drying: In good drying conditions: Touch dry in 2 hours. Allow 6 hours between coats. Ensure adequate ventilation during the drying period.

Limitations:

Do not apply in temperatures below 8°C or in damp or humid conditions. Only rarely used for the decoration of walls and ceilings. Seek Technical Advice.

Preparation:

All surfaces should be sound, dry, clean, and free from dirt, oil, grease or other contamination. New woodwork should be primed with an appropriate acrylic Wood Primer. Existing paintwork in sound condition should be washed down with a warm water detergent solution, thoroughly rinsed off and then lightly abraded. It is recommended that trials be carried out well in advance to ensure that the surface is suitable for application.

Application:

Stir gently before use. Water Based Eggshell is best applied by brush. Maintain wet edge. Two full coats normally recommended. Thinning should not be necessary for primed or previously painted surfaces. Only if absolutely necessary dilute by no more than 10% water and stir thoroughly.

Coverage:

12-14 m<sup>2</sup>/litre/coat on smooth surfaces of low porosity.



Cleaning: Brushes and equipment should be cleaned with warm soapy water

immediately after use.

**Technical Advice:** Product and Health and Safety data can be printed from our website:

www.roseofjericho.co.uk. Further assistance is available from our

Technical Department on 01935 83676.

Disclaimer: The information provided in this product data sheet and all technical

advice is for guidance and is given in good faith but without warranty, since the site conditions and care and skill of application are beyond our control. We can accept no liability for the performance of our products, beyond the value of the paint itself. This does not affect your

statutory rights.