



TECHNICAL DATA SHEET

Natural Cement

RJ 1.09

Description:

Prompt Natural Cement is a beige-coloured fast-setting and quick hardening hydraulic binder, produced by the calcination of an argillaceous (clay-rich) limestone at a moderate temperature (<12000C), followed by very fine grinding. It consists mainly of calcium aluminates, calcium sulphoaluminates and calcium silicates that should not be alite (C3S).

Uses:

Prompt Natural Cement is waterproof and is used where this and the fast-setting properties are an advantage, such as for the maintenance of sea walls in tidal locations. It is being increasingly used for the repair of 'Roman cement' renders and mouldings as it is the closest currently available binder. The rapid setting can be delayed by the addition of 'Tempo' citric acid retarder.

Availability:

Vicat Prompt Natural Cement. 25kg bags

Shelf Life:

Up to 3 months in original un-opened bags kept in DRY storage.

Observations:

Prompt Natural cement is a specialist product. Tradesmen familiar with the mixing and use of Natural cement and experience of its successful use should be employed. Accurate volumetric site mixing is essential. Prompt Natural Cement sets by the hydration of the hydraulic components and not by carbonation. However, the control of the drying and curing process by mist-spraying to keep moist, 'tending' to prevent shrinkage crazing and protecting is crucial to success and long-term performance. Protections are essential. Do not use if there is risk of excessive heat or frost.

Health & Safety:

See Health and Safety Data Sheet RJ 5.01 C.
Alkali (pH 13).

Danger: H318 Causes Serious Eye Damage.
H315 Causes skin irritation.

Warning: H335 May cause respiratory irritation.



Regulatory Information:

Danger symbol: Xi irritant product
Risk phases: R36/37/38 Irritating to eyes, respiratory system and skin.
R43 May cause sensitization by skin contact (Cr 6+)

Safety phases: S2 Keep out of the reach of children.
S24/25 Avoid contact with the skin and eyes
S26 In case of contact with eyes, rinse immediately with plenty of water and obtain medical advice.
S37 Wear suitable gloves.

Technical Advice:

From our Technical Department
01935 83676
info@roseofjericho.co.uk
All product and H & S data can be printed from our web site:
www.roseofjericho.co.uk

Disclaimer:

The information provided in this product data sheet and all technical advice is for guidance and is given in good faith but without warranty, since the site conditions and care and skill of application are beyond our control. We can accept no liability for the performance of our products, beyond the value of the material supplied. This does not affect your statutory rights.