



TECHNICAL DATA SHEET

Roman Cement

RJ 2.06

Description:

Roman Cement is a term used to describe certain hydraulic binders produced by the calcination in a coal fired kiln of limestones containing clay minerals (principally iron, alumina and silica). The name was adopted in c.1800 because the typical red-brown colour was thought to resemble mortars of the Roman period.

Roman cement was first produced in 1794 by James Parker from the clay-rich septaria of Harwich but similar products including 'Medina' and 'Sheppey' cements were subsequently produced from the septaria of the Solent and Thames estuary. These were not supplied as hydrates but mixed with water and sand on site when much heat was produced. They were fast-setting materials much used for run and cast mouldings and external renders.

True Roman Cements are no longer available and Roman cements are now based on Natural Hydraulic Lime (RJ 1.05) or Prompt Natural Cement (RJ1.09) mixed on site with carefully blended aggregates to match the colour and properties of the original. It is normally necessary to analyse the existing material (RJ 6) in order to design an accurate matching mix recipe.

Uses:

For the repair or reinstatement of Roman Cement renders and mouldings.

Availability:

Hydraulic Lime and Natural Cement normally ex stock.

Shelf Life:

Hydraulic limes deteriorate with age. Use fresh material.



Observations:

Tradesmen familiar with the Lime Method, and with experience of the successful use of hydraulic lime or natural cement should be employed. Accurate volumetric site-gauging and thorough mixing is essential. The control of the drying and curing process by keeping moist by mist-spraying to promote carbonation, 'tending' to prevent shrinkage crazing, and protecting is crucial to success and long-term performance. Protections are essential. Do not use in excessive heat or if there is risk of frost.

Health & Safety:

See Health and Safety Data Sheet RJ 5.01 A.
CALCIUM HYDROXIDE Ca(OH)_2 Alkali (pH 13).
CAS No. 85117-09-5. EINECS No. 285-561-1.
Danger: H318 Causes Serious Eye Damage.
Warning: H315 Causes skin irritation.
STOT SE3 H335 May cause respiratory irritation.

Technical Advice:

From our Technical Department 01935 83676
info@roseofjericho.co.uk
Product + H & S data can be printed from our web site:
www.roseofjericho.co.uk

Disclaimer:

The information provided in this product data sheet and all technical advice is for guidance and is given in good faith but without warranty, since the site conditions and care and skill of application are beyond our control. We can accept no liability for the performance of our products, beyond the value of the material supplied. This does not affect your statutory rights.